

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>E21B 43/08, 43/10, 43/04, B01D 29/58, 39/14, 39/08, 39/10</b>		A2	(11) International Publication Number: <b>WO 97/17524</b>
			(43) International Publication Date: 15 May 1997 (15.05.97)
(21) International Application Number: PCT/EP96/04887			(72) Inventors: DONNELLY, Martin; Badhuisweg 3, NL-1031 CM Amsterdam (NL). EMMEN, Jacobus, Hendrikus, Petrus, Maria; Volmerlaan 6, NL-2288 GD Rijswijk (NL). KENTER, Cornelis, Jan; Volmerlaan 6, 2288 GD Rijswijk (NL). LOHBECK, Wilhelmus, Christianus, Maria; Volmerlaan 6, NL-2288 GD Rijswijk (NL). REIJNEN, Paulus, Hermanus, Franciscus; Volmerlaan 6, NL-2288 GD Rijswijk (NL). ROSS, Brent, Reynolds; Volmerlaan 6, NL-2288 GD Rijswijk (NL). SAMUEL, Allan, James; Volmerlaan 6, NL-2288 GD Rijswijk (NL).
(22) International Filing Date: 7 November 1996 (07.11.96)			
(30) Priority Data: 95203038.5 8 November 1995 (08.11.95) EP			
(34) Countries for which the regional or international application was filed: GB et al.			
(71) Applicant (for all designated States except CA): SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).			
(71) Applicant (for CA only): SHELL CANADA LIMITED [CA/CA]; 400 - 4th Avenue S.W., Calgary, Alberta T2P 2H5 (CA).			(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).
Published Without international search report and to be republished upon receipt of that report.			

(54) Title: DEFORMABLE WELL SCREEN AND METHOD FOR ITS INSTALLATION

(57) Abstract

A deformable well screen for preventing migration of solid particles into a hydrocarbon production well comprises at least one substantially tubular filter layer of which the sieve opening size remains fairly constant or gradually changes in a predetermined and uniform manner during or after expansion and/or other deformation of the screen. Optionally the screen comprises a series of circumferentially scaled filter segments (4) that are arranged around an expandable slotted tube (3), an expandable slotted tube of which the slots are filled with resin coated granules, an expandable slotted tube with micro-slots, an assembly of woven metal wire screens that are sintered together and/or a synthetic geotextile.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LJ	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

- 1 -

**DEFORMABLE WELL SCREEN AND METHOD FOR ITS INSTALLATION**

The invention relates to a well screen for preventing migration of solid particles, such as sand and other formation minerals, gravel and/or proppant, into a hydrocarbon production well.

5       More particularly, the invention relates to a well screen comprising at least one substantially tubular filter layer of which the sieve opening size is tailored to the size of particles that are to be blocked by the screen.

10       Such a screen is known, for example, from UK patent specification 2115040. The known screen may further comprise outer and/or inner protective layers which are co-axial to the filter layer and which have a much larger sieve opening size than the filter layer or layers.

15       A problem encountered with the known screen is that woven metal wire and other filter sheets are fragile and can be easily squeezed and damaged during installation and use.

20       Only a minor deformation of the filter sheet may already result in variation of the sieve opening which may hamper a proper performance of the screen.

25       Furthermore sand screens of the known type are typically made in a flat or tubular shape and are designed to remain in their original shape without substantial deformation during and/or after installation. However, in boreholes with an irregular surface and/or sharp bends this requires the use of a screen with a much smaller diameter than that of the wellbore. Such use of a small diameter screen will result in high fluid flowrates through the sieve openings of the screen, strong wear of

30

- 2 -

the screen and an increased risk of plugging of the screen and of collapse of the borehole.

It is an object of the invention to alleviate these problems.

5       The screen according to the invention thereto is deformable such that it can be expanded, bent, compressed and/or fluidized during installation of the screen within a wellbore and that any variation of the sieve opening size of the screen as a result of such deformation  
10       remains within predetermined limits.

      It is preferred that the screen is radially expandable by moving an expansion mandrel in an axial direction through the interior of the screen and the sieve opening size of each tubular filter layer remains  
15       fairly constant or varies in a predetermined and uniform manner during expansion and/or other deformation of the screen.

      Preferably the screen is expandable downhole to such a size that it, or a surrounding protective layer,  
20       can be set at least partly against the surrounding formation or perforated casing. At locations, such as washouts and doglegs, where the borehole wall is so irregular that still a gap would remain around the expanded screen a resin impregnated gravel could be  
25       placed in the gap to ensure a continuous mechanical contact between the screen and formation.

      Optionally the screen according to the invention is arranged around an expandable slotted tube which induces the internal diameter of the screen to be increased  
30       during installation of the screen and tube assembly in a wellbore while the variation in sieve opening size of each filter layer of the screen as a result of such expansion of the screen is less than fifty per cent.

- 3 -

A suitable expandable slotted tube for use with the screen is disclosed in the specification of international patent application PCT/EP 93/01460.

5 This prior art reference discloses that a wrapping such as a sintered metal screen or membrane may be applied around an expandable slotted liner to prevent sand from entering the borehole, but it does not teach to create a wrapping which is itself expandable. Said prior art reference also discloses that by arranging co-axial  
10 expandable slotted tubes such that the slots are not aligned sand inflow may be prevented. Such arrangement does not yield, however, a well defined and uniform screen opening size throughout the length of the expanded tubes.

15 In a preferred embodiment the screen according to the invention comprises a series of scaled filter sheets which are arranged around an expandable slotted carrier tube and which, when seen in a circumferential direction, are connected at one edge to said tube and at another  
20 edge at least partly overlap an adjacent filter sheet. Optionally the scaled filter sheets are made of a flexible permeable material which is selected from the group of a perforated metal plate, a metal plate comprising an array of substantially tangential slots,  
25 sintered woven metal wires and a synthetic fabric.

In another preferred embodiment the screen according to the invention comprises an expandable slotted tube of which the slots and any gaps between the tube and borehole wall have been filled in situ with granules that  
30 are bonded to each other and to the rims of the slots by a bonding agent such that pore openings of a selected size remain between the granules.

In the above embodiments the slotted tube can be expanded to a diameter which may be 50% larger than the  
35 diameter of the unexpanded tube. The sieve opening size

- 4 -

of the screen remains substantially unaffected by such large expansion although the scaled filter sheets may be stretched in a circumferential direction as a result of frictional forces and deformed slightly by the axial contraction of the slotted carrier tube during the expansion process.

In a suitable embodiment the screen according to the invention comprises

- at least one tubular filter layer which is made of a woven metal wire screen; and
- an outer protective layer which co-axially surrounds the filter layer or layers and an inner protective layer which is fitted co-axially within the protective layer or layers, which protective layers comprise each a woven metal wire screen having a larger sieve opening size and wire thickness than at least one of the filter layers, and wherein the filter and protective layers are sintered together.

A principal advantage of sintering the various layers of woven metal wire screen together is that it produces a screen having a section modulus which is greater than the sum of section moduli of the individual layers. This results in a robust screen of which the sieve size does not change significantly during or after deformation which make the screen coilable around a drum and installable into a well by reeling the screen from the drum.

Optionally at least one filter layer comprises wires which are oriented in a substantially helical weaving pattern relative to a central axis of the tubular screen.

It has been found that if said pitch angle is approximately  $45^\circ$  then local elongation and/or shortening caused by expansion, compression and/or bending of the tubular screen then a square mesh sieve will be deformed to a diamond pattern, and the sieve

- 5 -

opening will only change slightly and by a predictable amount.

A tubular screen having a helical weaving pattern can be conveniently manufactured from sheets or strips having the wires substantially parallel and normal to the edges, by forming those sheets or strips into a helically wound tubular shape having abutting edges, and welding the abutting edges together, as is done for example for helically welded metal tubes.

It is observed that SU patent specification No. 1,066,628 discloses that a screen can be made by scrolling six layers of metal filtration cloth around a perforated metal tube and then sintering the pack. However, in the known screen the various layers are made of the same cloth. This will generally cause the wires of adjacent layers to partly block the sieve openings of adjacent layers which will reduce the effective sieve opening in a rather irregular and unpredictable way.

Other screens are disclosed in US patent specification Nos. 2,858,894 and 3,087,560 and in a sales brochure of Haver and Boecker concerning screens sold under the trademark "POROPLATE".

It is observed that US patent No. 3,353,599 discloses the use of a corrugated liner which is brought into a tubular shape by an expansion mandrel and that US patent Nos. 2,812,025 and 3,270,817 disclose spring actuated expandable permeable well liners. The use of a corrugated liner or a spring mechanism, however, may cause large forces during the expansion process which may damage the screen provided by the expanded liner.

In an alternative embodiment of the screen according to the invention the screen comprises at least one filter layer which is substantially made of a fabric, such as a needlefelt. Suitably the needlefelt



- 6 -

comprises a material selected from the group of steel wires and synthetic fibres. Optionally the synthetic fibres are selected from the group of aramid fibres and "CARILON" polymer fibres which have a high chemical resistance. "CARILON" polymer is a linear alternating copolymer of carbon monoxide and one or more olefinically unsaturated compounds. European patent specifications Nos. 360,358 and 310,171 disclose methods for the manufacture of fibres of this polymer by gel and melt spinning, respectively. Preferably the filter layer comprises an elongate fabric strip which is wound in an overlapping helical pattern into a tubular shape, whereby adjacent windings have an overlap of between 10% and 90%, preferably about 50%.

It is observed that international patent application PCT/EP/01460 discloses that two co-axial slotted liners may be placed within the wellbore such that after expansion the slots are not in line in radial direction. This non-aligned slot arrangement aims to induce fluids to traverse through the liners via a zig-zag path thereby preventing sand from entering the borehole. The liners used in this prior art reference comprised axial slots having a length of at least 25 mm and a width of at least 0.7 mm. Although this known arrangement does reduce sand inflow into the borehole it does not create a sand screen having a uniform and well defined screen opening size.

Surprisingly it was found that instead of using the interaction between non-aligned relatively large slots of co-axial liners to prevent inflow of sand a suitable screen may be created by using a single expandable tube having micro-slots.

Therefore, in yet another alternative embodiment of the screen according to the invention the screen comprises an expandable tubular body with micro-slots that are arranged in a staggered and overlapping pattern

- 7 -

which slots substantially have a length less than 10 mm before expansion of the tubular body.

Preferably the micro-slots substantially have before expansion of the tubular body a length less than 5 mm and a width less than 0.3 mm.

A principal advantage of the use of a single expandable sand-screen with micro-slots over the use of co-axial liners with non-aligned relatively large slots is that it generates a screen with a more regular substantially diamond-shaped sieve opening size after expansion.

Suitably the expandable tubular body with micro-slots is made of nickel and has a wall thickness which is less than 1 mm. In order to protect such a fragile body from damage during and after installation it is preferred to arrange the body co-axially between two conventional expandable slotted liners having larger slots and a larger wall thickness than the body. Suitably these protective liners are made of steel and comprise slots having a length of at least 15 mm and a width of at least 2 mm.

It is observed that US patent specification 1,135,809 discloses a well screen with staggered axial slots. The screen according to this prior art reference, however, is installed downhole without being subject to any significant expansion or other deformation, so that the slots remain in their original elongate shape.

The invention also relates to a method for installing a tubular well screen in a hydrocarbon production well, the method comprising arranging the screen around an expandable slotted tube, lowering the screen and tube assembly into the well, inducing the tube to expand by axially moving an expansion cone therethrough, thereby increasing the internal diameter of the screen with at least five per cent while any variation of the sieve

- 8 -

opening size of each filter layer of the screen is less than fifty per cent.

Optionally the screen and tube assembly is wound around a drum and reeled from said drum into the well during installation.

It is observed that European patent application No. 674 095 discloses a well screen which is reeled from a drum during installation. This known screen is not expanded, however, during the installation process.

In an alternative embodiment the method according to the invention comprises lowering an expandable slotted tube into the well, inducing the tube to expand, injecting granules coated with a bonding agent into the expanded tube and wiping the granules at least partly away from said interior into the expanded slots of the tube and any gaps that may be present between the expanded tube and the borehole wall, and allowing the bonding agent to cure. In this way a permeable matrix of bonded solid particles is formed which substantially fills the expanded slots and any gaps between the expanded tube and the borehole wall.

The coated granules may consist of resin coated granules having a diameter between 1 and 5 mm which are injected via injection parts located behind the expansion cone and a wiper set may be trailed behind the cone in order to wipe the granules from the interior of the expanded tube into the slots and any gaps surrounding the tube.

These and other features, objects and advantages of the method and screen according to the invention will become apparent from the accompanying claims, abstract and the following detailed description.

The invention will now be described in more detail with reference to the drawings and other examples that are not illustrated.

- 9 -

In the accompanying drawings:

Fig. 1 shows a cross-sectional view of a segmented screen which is lowered into a well between two unexpanded slotted tubes;

5 Fig. 2 shows a cross-sectional view of the screen and tube assembly of Fig. 1 after expansion of the assembly;

Fig. 3 is a side view of a section of one of the filter sheets of the segmented screen of Fig. 1 and 2 shown at an enlarged scale;

10 Fig. 4 is a side view of a section of the unexpanded slotted carrier and protective tube of Fig. 1 shown at an enlarged scale;

Fig. 5 is a side view of a section of the expanded carrier and protective tube of Fig. 2 shown at an enlarged scale; and

15 Fig. 6 is a schematic longitudinal sectional view of an expanding slotted tube where resin coated granules are wiped into the slots to form, after curing of the resin, a sandscreen.

20 Referring now to Fig. 1 and 2 there is shown a borehole 1 passing through an underground hydrocarbon bearing formation 2.

An assembly of an expandable slotted carrier tube 3, a well screen comprising four scaled perforated filter sheets 4 and an expandable slotted protective tube 5 has  
25 been lowered into the borehole 1.

Each filter sheet 4 is connected near one edge to the carrier tube 3 by a lug 6 such that at an opposite edge it overlaps an adjacent sheet 4.

30 The lugs 6 permit the filter sheets 4 to move axially with respect to the carrier tube 3 and in that way to enable the axial contraction of the carrier tube 3 as a result of tangential expansion to be compensated for by axial sliding of the filter sheets 4 over the carrier  
35 tube.

- 10 -

In Fig. 1 the assembly is in an unexpanded form so that the slots 7 of the two slotted tubes 3 and 5 have an elongate longitudinal shape and a constant width, when seen in circumferential direction as shown in Fig. 4, the filter sheets 4 in a longitudinal direction the sheets may also be wrapped helically around the carrier tube 3 at such pitch angle that the sheet will contract during the expansion in longitudinal direction in substantially the same way as the slotted tube 3.

During the expansion process adjacent filter sheets 4 will slide relative to each other and the sheets 4 will also slide relative to the inner wall of the protective tube 5.

In the embodiment shown the sheets 4 are made of a perforated nickel foil which is a low friction material.

In order to further reduce friction during expansion the filter sheets 4 may comprise substantially tangential slots instead of the circular perforations shown in Fig. 3. The width of such tangential slots will not change significantly during expansion of the assembly within the borehole 1.

Instead of using a nickel foil for the filter sheets 4 these sheets may also be made of another material, such as a sintered woven wire mesh and a synthetic fabric which are described in more detail elsewhere in this specification.

Instead of using a slotted steel protective tube 5 around the filter sheets 4 any other expandable and permeable protective tubular body may be used, such as a knitted geotextile sock or a scrolled perforated metal sheet. Instead of using a plurality of filter sheets which each only partly surround the carrier tube 3 also a single scrolled filter sheet may be used which is not secured. As an alternative to using lugs 6 for connecting the filter sheets 4 to the carrier tube 3, the sheets 4

- 11 -

may be spot welded or connected by other mechanical fasteners to the carrier tube.

5 Instead of connecting each filter sheet 4 at its inside edge to the carrier tube 3 as shown in Fig. 1 it may also be connected near its mid-line to the carrier tube 3 to distribute any distortion and frictional forces exerted to the sheets 4 during the expansion process.

10 In Fig. 2 the assembly is shown in an expanded form so that the slots 7 of the slotted tubes 3 and 5 have a diamond shape as can be seen in Fig. 5. Expansion of the assembly may be accomplished by moving an expansion cone through the steel carrier tube 3 as described in international patent application PCT/EP93/01460, whereby the expansion of the carrier tube also induces the outer tube 5 to expand until it substantially engages the borehole wall.

20 During the expansion process overlap between adjacent filter sheets 4 is reduced, but the circumferential length of the scaled sheets 4 is selected sufficiently large that still at least some overlap remains after the expansion.

25 As illustrated in Fig. 3 the filter sheets 4 consist of perforated plates and the width of the perforations remains substantially the same during and after the expansion process. However, the carrier tube 3 will contract slightly in longitudinal direction as a result of the expansion process. Therefore it is preferred to arrange the lugs 6 within slots which permit the lugs 6 to slide in longitudinal direction relative to the carrier tube 3. However instead of using lugs the front edges of the filter sheets 4 may also be secured to the carrier tube 3 by spot welding. In such case this may result in some longitudinal compaction of the front edges of the filter sheets during the expansion process if these front edges have a longitudinal orientation.

30

35

- 12 -

However, alternatively the front edges of the filter sheets 4 may have a helical orientation relative to the carrier tube 3. In such case one or more filter sheets 4 may be wrapped helically around the carrier tube 3 such that opposite edges of the filter sheet overlap each other both in the unexpanded and the expanded position of the carrier tube 3.

Fig. 6 shows an embodiment of the screen according to the invention where a screen is formed in situ within the borehole. An expandable slotted steel tube 10 is expanded against the borehole wall 11 by pulling an expansion cone 12 upwardly through the tube 10.

The cone 12 is suspended at the lower end of a coiled tubing 13 via which resin coated granules 14 are injected which pass via injection ports 15 just below the cone 12 into the interior of the expanding tube 10. A set of two disk-shaped wipers 16 is trailed behind the cone by a rod 17 which press the granules 14 out of the interior of the expanded tube 10 into the expanded slots 18 and any gaps 19 that may be present between the borehole wall 11 and the expanded tube 10. After curing of the resin the granules are bonded to a permeable matrix of granules which fills the expanded slots 18 and which is also bonded to the rims of these slots 18. The diameter of the granules 14 is selected such that the pores between the granules 14 form sieve openings of a size suitable to prevent ingress of sandgrains into the well. For most sandgrain sizes a suitable granule size is between 0.5 and 5 mm.

Another deformable well screen was constructed from seven layers of wire mesh woven in a plain rectangular weave pattern with respectively the following sieve opening sizes: 5000/950/162/625/325/950/5000  $\mu\text{m}$ .

- 13 -

These layers were sintered together in a vacuum to form a plate, which was then rolled into the form of a tube and seam welded.

5 The layers consisted of sheets of woven wire mesh of 350 mm long and 170 mm wide which were sintered together in a vacuum furnace between two plates of cordierite ceramic. These plates were pressed together by a 9 kg weight. The material was sintered for four hours at 1260 °C and a pressure of  $10^{-4}$  Pa. The material was  
10 allowed to cool in the furnace under vacuum.

After the sintering procedure the stack of layers was about 9 mm thick. It was then rolled in a rolling mill to a thickness of 5 mm in one pass and sintered for a further four hours under the same conditions.

15 The sintered plate was subsequently cut to a length of 310 mm and placed in a 3-roll bending machine with the 170 mm edge parallel to the roll axis and rolled to make a tube of about 100 mm diameter and 170 mm long.

The seam was then brazed. However, if desired, it  
20 would have been possible to weld the seam. In the thus created tubular screen the layers with the sieve opening sizes of 162 and 325  $\mu\text{m}$  acted principally as the filter layers whereas the other layers, viz those with sieve opening sizes of 625, 950 and 5000  $\mu\text{m}$  acted essentially as  
25 protective layers. The filter layer with the finest sieve opening size, i.e. 162  $\mu\text{m}$ , surrounded the filter layer with the coarser sieve opening size, i.e. 325  $\mu\text{m}$ , to reduce sand accumulation within the screen.

30 The following tests were carried out with sintered woven wire sieve plates according to the invention.

A short length of a tubular sieve plate was axially compressed between platens in a press to reduce its length by 10%. The tube walls showed incipient buckles. No obvious changes in sieve opening size were found in a  
35 visual inspection. The length changes in the finest mesh



- 14 -

accommodated by bulging outwards between the wires of the coarser mesh, with apparent retention of weave pattern and sieve opening dimensions.

5 Furthermore a disc of sintered mesh was placed in a 0,5 m long cell, 50 mm diameter, containing 1500 g sand from a hydrocarbon fluid production well in Uiterburen, the Netherlands. Air at 100 bar was flowed through the sand bed and the screen for a week at a nominal velocity through the screen of 5 m/s. The pressure drop over sand  
10 bed and screen remained constant at 3 bar.

The weight of the sand recovered from the cell after the test was 9 g less.

It was concluded from this test that the screen stabilized the sand sufficiently to prevent significant  
15 migration of the fine sand. Further the screen was not plugged to the extent that a significant increase in pressure drop resulted.

It was also concluded that the combination of protective layers having a coarse mesh and made from  
20 thick wire with filter layers with fine mesh that are sintered together creates a robust structure with a fine sieve size. Sintering the various layers together produces a screen having a section modulus which is greater than the sum of section moduli of the individual  
25 layers.

The weaving patterns and wire gauges in the various layers can be selected to give the desired combination of strength and compliance in radial, circumferential and longitudinal directions so that the screen can be made as  
30 a self supporting tube which can be reeled from a drum into the well and then expanded downhole.

If the predominant weaving pattern has its warp axis parallel to the tube axis and the warp threads are bent over and under the weft threads, while the latter are  
35 relatively undistorted (as for example in reversed plain

- 15 -

Dutch weave or reversed Dutch twill) then the yield strain in longitudinal bending will be relatively high but at relatively low stress, and the tube can be easily bent; while if the weft threads are bent and the warp threads straight (plain Dutch weave or Dutch twill) the tube can be more easily expanded or reduced in diameter. If the warp and weft threads are at an angle of 45 ° to the tube axis (as in helically welded tube) then a square mesh weave will be deformed to a diamond pattern as a result of any deformation causing length or diameter changes, and the sieve aperture will only change slightly and by a predictable amount. If two layers of the fine mesh are separated by coarse mesh, sand eroding the first layer will accumulate in the space between the two layers and offer some protection against erosion to the second layer, not only by forming a barrier but also by locally reducing the permeability and hence the flow. If the outermost fine mesh has a smaller sieve opening size than the next fine layer, then any material which passes through the outer fine layer may also pass through subsequent fine layers, reducing the tendency of the screen to internal plugging. Preferably the sieve opening size of the outermost filter layer is at least two times smaller than any of the other filter and protective layers.

Yet another deformable well screen was made of a non-woven needlefelt consisting of aramid fibres which is marketed by the company Duflot under the trademark "KEVLAR" EA 205.

The needlefelt was 4 mm thick, had a weight of 400 g/m<sup>2</sup> and was manufactured by needle punching.

A needlefelt sheet was brought into a tubular shape and the engaging ends of the sheet were stitched together. The thus formed tubular screen was then arranged around an expandable slotted tube which

- 16 -

initially had an internal diameter of 38 mm. The tube was subsequently expanded to an internal diameter of 80 mm. Before and after the expansion the wall thickness of the tube was 5 mm. The force required to pull a cone through the tube in order to expand the tube and screen assembly was 30 KN. This is 6 KN more than the force required for expansion of the expandable slotted tube alone.

The expansion of the screen did not cause any damage to the needlefelt or to the stitches. The thickness of the needlefelt was reduced by 37.5%.

The expanded tube and screen assembly had a length of 285 mm and was placed in a tubular container with a 30 mm thick annular layer of sand around the screen.

The sand was 0-0.1 mm sand from a hydrocarbon well in Pekela, the Netherlands. The sand had a permeability  $K = 2.10$  Darcy and a porosity  $n(p) = 42.39\%$ .

Water was pumped radially via six injection points through the annular sand pack and screen into the interior of the expanded tube and then circulated back during a period of six hours.

During the test the fluid pressure inside the tube was about 2.6 bar and the fluid pressure at the injection point was about 2.7 bar.

The water flux through the screen was 5 l/min. Throughout the test no sand was detected in the circulated water and the pressure drop across the sand pack and screen remained constant at about 0.1 bar. From the test it was concluded that the expansion of the screen had caused no significant effect on the performance of the screen as a sand filter and that thus only minor variations in sieve opening size of the screen had occurred as a result of the expansion.

- 17 -

The test was repeated with a silt fraction of 15  $\mu\text{m}$  to 63  $\mu\text{m}$ , smeared onto the screen, which yielded a similar favourable result.

5 Further the longevity of the needlefelt screen was tested by clamping it between steel plates with circular holes of various sizes. The steel plates were located such that the corresponding holes in the respective plates were co-axial. The plates with the needlefelt exposed at the location of the holes were  
10 then sandblasted for substantial periods.

No damage to the needlefelt screen was observed after the test for the holes smaller than 5 mm diameter.

15 It was concluded from the various tests that a needlefelt or other geotextile fabric is suitable for use as a deformable sandscreen. It was also concluded that such a screen can be made and installed in a cost-effective manner by arranging a tubular fabric layer between two perforated co-axial pipes. Such an assembly  
20 of fabric layer and pipes can be reeled on a drum and transported to the wellsite, where the assembly is reeled from the drum into the well. The fabric layer may consist of an elongate strip which is wound helically around the inner perforated pipe such that  
25 adjacent windings of the strip at least partly overlap each other.

The above assembly is particularly attractive if a screen of substantial length is to be installed in a compacting reservoir.

30 Alternatively a tubular needlefelt or other fabric layer is arranged between a pair of co-axial expandable slotted tubes. In such case the fabric may also consist of a strip which is wound helically around the inner expandable tube such that a substantial overlap exists

- 18 -

between adjacent windings of the strip before expansion of the tubes.

5 The overlap is in such case selected sufficiently large that after expansion of the assembly at least some overlap remains between adjacent windings of the fabric strip.

10 Reference is now made to yet another embodiment of the deformable tubular well screen according to the invention which is not illustrated. In this embodiment the screen comprises a tubular screen in which axial slots are present, which slots are regularly distributed in a staggered partly overlapping pattern over the surface of the screen. The tested screen was made of a nickel tube which had before expansion an  
15 internal diameter of about 145 mm and a wall thickness of 0.66 mm. The slots each had a length of about 3.5 mm and a width of 0.15 mm before expansion. The slots were pitched 5 per 24.5 mm longitudinally and 17 per 24.5 mm circumferentially, the longitudinal axis of the slots being parallel to the tube.

20 One millimetre thick steel protective expandable slotted tubes were co-axially arranged within and around the screen. The protective tubes each comprised slots having before expansion a length of about 20 mm and a width of about 2.2 mm. The slots in these  
25 protective tubes were pitched at 24 mm longitudinally and 4.2 mm circumferentially.

30 A 2 m long assembly of the nickel sand screen and steel protective screen was arranged within a steel casing having an internal diameter of about 160 mm and in which nine inspection holes having a diameter of about 30 mm were present.

35 The assembly was expanded against the inner wall of the casing by pulling a cone through the assembly. Visual examination of the assembly demonstrated a tight fit

- 19 -

between the assembly and casing and a substantially uniform expansion of the protective tubes and the nickel sand screen. As a result of the expansion the slots of the nickel sand screen had opened up to a diamond shape and the smallest width of the slots was between 0.3 and 0.4 mm. It was concluded that small variations in the slot widths were due to slight variations in the exact amount of expansion and that these variations were within acceptable limits.

A flow test was carried out during which tap water was allowed to flow via three inspection holes through the screen at rates of between 8 and 10 litres per minute. During the test the pressure drop across the screen remained between 0.1 and 0.2 bar.

A ten metre long version of this screen was installed and tested in an oil well in Oman. The production data show that not only does the screen control sand production without the need for gravel packing but also that the well's productivity is unimpaired compared to its productivity before installation of the screen. The screen also showed no signs of plugging over a sustained period of production.

- 20 -

CLAIMS

1. A deformable well screen for preventing migration of solid particles into a hydrocarbon production well, which screen comprises at least one substantially tubular filter layer having a sieve opening size which is  
5 tailored to the size of particles that are to be blocked by the screen, which filter layer is deformable such that it can be expanded, bent, compressed and/or fluidized during installation of the screen in a wellbore and that any variation of the sieve opening size of each filter  
10 layer as a result of such deformation remains within predetermined limits.
2. The well screen of claim 1, wherein the screen is radially expandable by moving an expansion mandrel in an axial direction through the interior of the screen and  
15 the sieve opening size of each tubular filter layer remains fairly constant or varies in a predetermined and uniform manner during expansion and/or other deformation of the screen.
3. The well screen of claim 1 or 2, wherein the well  
20 screen is coilable around a drum and installable into a well by reeling the screen from the drum.
4. The well screen of claim 1, 2 or 3, wherein the filter layer comprises a series of scaled filter sheets which are arranged around an expandable slotted carrier  
25 tube and which, when seen in a circumferential direction, are connected at or near one edge to said tube and at another edge at least partly overlap an adjacent filter sheet.
5. The well screen of claim 4, wherein the filter sheets  
30 are connected to said carrier tube by a series of lugs that are hooked onto the carrier tube and wherein an

- 21 -

expandable slotted protective tube surrounds the filter layer.

6. The well screen of claim 4 or 5, wherein the filter sheets are made of a flexible permeable material which is selected from the group of a perforated metal plate, a metal plate comprising an array of substantially tangential slots, a sintered woven metal wire and a synthetic fabric.

7. The well screen of claim 1, 2 or 3, wherein the filter layer comprises an expandable slotted tube of which the slots and any gaps between the tube and borehole wall have been filled in situ with granules that are bonded to each other and to the rims of the slots by a bonding agent such that pore openings of a selected size remain between the granules.

8. The well screen of claim 1, 2, 3 or 7, wherein the screen comprises an expandable tubular body with longitudinal micro-slots that are arranged in a staggered and overlapping pattern, which micro-slots substantially have before expansion of the tubular body a length less than 10 mm.

9. The screen of claim 8, wherein the tubular body is made of nickel and the micro-slots substantially have a length less than 5 mm and a width less than 0.3 mm.

10. The well screen of claim 1, 2 or 3, comprising

- at least one deformable tubular filter layer which is made of a woven metal wire screen; and
- an outer protective layer which co-axially surrounds the filter layer or layers and an inner protective layer which is fitted co-axially within the protective layer or layers, which protective layers comprise each a woven metal wire screen having a larger sieve opening size and wire thickness than at least one of the filter layers, and wherein the filter and protective layers are sintered together.



- 22 -

11. The well screen of claim 10, wherein at least one filter layer comprises wires which are oriented in a substantially helical weaving pattern relative to a central axis of said layer.
- 5 12. The well screen of claim 11, wherein a helix defined by the helical weaving pattern is oriented at a pitch angle between 40 ° and 50 ° relative to said central axis.
- 10 13. The well screen of claim 11 or 12, wherein the screen comprises filter sheets that are brought into a helical shape and welded together in a substantially non-overlapping helical pattern.
- 15 14. The well screen of any one of claims 10-13, comprising an inner and an outer filter layer which are co-axial to each other and separated by an intermediate layer which is made of a woven wire having a larger sieve opening than the filter layers and which is sintered to the filter layers, and wherein the outer filter layer has a smaller sieve opening than the inner filter layer.
- 20 15. The well screen of claim 14, wherein a pair of outer protective layers surrounds the outer filter layer and a pair of inner protective layers is fitted within the inner filter layer and wherein the outermost outer protective layer and the innermost inner protective layer have a larger sieve opening size than the other layers.
- 25 16. The well screen of claim 1, 2 or 3, wherein the screen comprises at least one filter layer which is substantially made of a fabric.
- 30 17. The well screen of claim 16, wherein the filter layer comprises an elongate fabric strip which is wound in an overlapping helical pattern to a substantially tubular shape.
- 35 18. The well screen of claim 16 or 17, wherein said fabric comprises a needlefelt comprising a material selected from the group of steel wires and synthetic


- 23 -

fibres, synthetic fibres selected from the group of aramid fibres and synthetic fibres selected from the group of "CARILON" polymer fibres.


- 5 19. A method of installing a deformable well screen in a hydrocarbon production well, the method comprising arranging the screen around an expandable slotted tube, lowering the screen and tube assembly into the well, inducing the tube to expand by axially moving an expansion mandrel therethrough, thereby increasing the
- 10 internal diameter of the screen with at least five per cent while any variation of the sieve opening size of each filter layer of the screen is less than fifty per cent.
- 15 20. The method of claim 19, wherein the screen and tube assembly is wound around a drum and reeled from said drum into the well during installation.
- 20 21. A method of installing a deformable well screen in a hydrocarbon production well, the method comprising lowering an expandable slotted tube into the well, inducing the tube to expand and the slots to open, injecting granules coated with a bonding agent into the expanded tube, wiping the granules substantially from the interior of the tube into the slots and any gaps between the tube and the wellbore, and allowing the bonding agent
- 25 to cure.
22. The method of claim 19, 20 or 21, wherein the screen is installed in a compacting hydrocarbon reservoir which induces the screen to deform gradually in longitudinal and other directions after installation.




**FIG. 2**




**FIG. 3**




**FIG. 4**



**FIG. 5**



**FIG. 6**



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification<sup>6</sup> : <b>E21B 43/08, 43/10, 43/04, B01D 29/58, 39/14, 39/08, 39/10</b></p>	<p><b>A3</b></p>	<p>(11) International Publication Number: <b>WO 97/17524</b></p>
		<p>(43) International Publication Date: 15 May 1997 (15.05.97)</p>
<p>(21) International Application Number: PCT/EP96/04887</p> <p>(22) International Filing Date: 7 November 1996 (07.11.96)</p> <p>(30) Priority Data: 95203038.5 8 November 1995 (08.11.95) EP (34) Countries for which the regional or international application was filed: GB et al.</p> <p>(71) Applicant (for all designated States except CA): SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).</p> <p>(71) Applicant (for CA only): SHELL CANADA LIMITED [CA/CA]; 400 - 4th Avenue S.W., Calgary, Alberta T2P 2H5 (CA).</p>	<p>(72) Inventors: DONNELLY, Martin; Badhuisweg 3, NL-1031 CM Amsterdam (NL). EMMEN, Jacobus, Hendrikus, Petrus, Maria; Volmerlaan 6, NL-2288 GD Rijswijk (NL). KENTER, Cornelis, Jan; Volmerlaan 6, 2288 GD Rijswijk (NL). LOHBECK, Wilhelmus, Christianus, Maria; Volmerlaan 6, NL-2288 GD Rijswijk (NL). REIJNEN, Paulus, Hermanus, Franciscus; Volmerlaan 6, NL-2288 GD Rijswijk (NL). ROSS, Brent, Reynolds; Volmerlaan 6, NL-2288 GD Rijswijk (NL). SAMUEL, Allan, James; Volmerlaan 6, NL-2288 GD Rijswijk (NL).</p> <p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p><b>Published</b> With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p> <p>(88) Date of publication of the international search report: 19 June 1997 (19.06.97)</p>	
<p>(54) Title: DEFORMABLE WELL SCREEN AND METHOD FOR ITS INSTALLATION</p>		
<p>(57) Abstract</p> <p>A deformable well screen for preventing migration of solid particles into a hydrocarbon production well comprises at least one substantially tubular filter layer of which the sieve opening size remains fairly constant or gradually changes in a predetermined and uniform manner during or after expansion and/or other deformation of the screen. Optionally the screen comprises a series of circumferentially scaled filter segments (4) that are arranged around an expandable slotted tube (3), an expandable slotted tube of which the slots are filled with resin coated granules, an expandable slotted tube with micro-slots, an assembly of woven metal wire screens that are sintered together and/or a synthetic geotextile.</p> <div data-bbox="673 1165 1380 1858"> </div>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LJ	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam



# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/EP 96/04887

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 E21B43/08 E21B43/10 E21B43/04 B01D29/58 B01D39/14  
B01D39/08 B01D39/10

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 E21B B01D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 93 25800 A (SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ) 23 December 1993 cited in the application see abstract	1,2
Y	see page 1, line 27 - line 29	8,9
Y	see page 6, line 19 - line 24	19-22
	---	
X	EP 0 674 095 A (NAGAOKA INTERNATIONAL CORPORATION) 27 September 1995 see column 7, line 33 - line 41 see column 4, line 7 - line 10	1,3,8,9
Y	see column 9, line 28 - line 35 see column 11, line 4 - line 39	19,20,22
	---	
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \*&\* document member of the same patent family

Date of the actual completion of the international search

24 April 1997

Date of mailing of the international search report

14.05.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+ 31-70) 340-3016

Authorized officer

Sogno, M

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/EP 96/04887

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 353 599 A (SWIFT) 21 November 1967 cited in the application	1,2,8
A	see column 4, line 46 - column 5, line 10	
A	see column 5, line 6 - line 7	19
	see column 4, line 67 - line 70	22
	---	
X	US 3 270 817 A (PAPAILA) 6 September 1966 cited in the application	1
	see column 4, line 21 - line 40	
	---	
X	US 1 380 182 A (BIGELOW) 31 May 1921 see page 1, left-hand column, line 52 - right-hand column, line 66	1
	---	
X	US 1 514 062 A (MC LAIN) 4 November 1924 see page 1, line 64 - line 93	1
	---	
X	US 2 812 025 A (TEAGUE) 5 November 1957 cited in the application	1
	see column 3, line 4 - line 11	
	---	
X	US 5 211 234 A (FLOYD) 18 May 1993 see abstract	1,7
Y		21
	---	
X	US 2 198 573 A (DAVIS) 23 April 1940 see page 3, left-hand column, line 49 - line 53	1
A		7,21
	---	
X	US 3 153 451 A (CHANCELLOR) 20 October 1964 see the whole document	1
A		7,21
	---	
X	US 3 637 010 A (MALY) 25 January 1972 see the whole document	1
A		7,21
	---	
X	DE 41 26 420 C (BERGWERKSVERBAND GMBH) 11 February 1993 see abstract	1,2
Y		8,9
	---	
X	US 3 633 674 A (BRIEGER) 11 January 1972 see column 2, line 30 - line 35	1
	---	
X	WO 94 28284 A (PALL CORPORATION) 8 December 1994 see page 10, line 30 - line 35 see page 11, line 28 - line 32 see page 13, line 7 - line 32 see page 14, line 9 - page 15, line 13 see page 8, line 33 - page 9, line 6 see page 11, line 24 - line 28	1,2, 10-15
Y		8,9
Y		17
	---	
	-/--	

# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/EP 96/04887

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 434 054 A (LIVESEY) 28 February 1984 see column 4, line 58 - line 63 see column 5, line 49 - column 6, line 2	1
A	---	10
X	US 2 858 894 A (AKEYSON) 4 November 1958 see the whole document	1
A	---	10
X	US 2 835 328 A (THOMPSON) 20 May 1958 see column 2, line 24 - line 27	1
A	---	10
X	US 2 877 852 A (BASHARA) 17 March 1959 see claim 1	1,16
A	---	10
X	GB 1 455 481 A (LOVELL) 10 November 1976 see page 1, line 39 - line 56	1,16
A	---	10
X	US 2 217 370 A (JOHNSTON) 8 October 1940 see claim 1	1
A	---	10
X	US 2 143 072 A (JOHNSON) 10 January 1939 see the whole document	1
A	---	10
X	DE 38 16 670 A (WUNDERTZKE) 29 December 1988 see abstract	1,16,18
X	GB 2 067 425 A (LUCAS INDUSTRIES LIMITED) 30 July 1981 see page 1, line 69 - line 73	1,16
Y	---	17
X	US 5 226 581 A (HODGE) 13 July 1993 see the whole document	1,16,18
X	EP 0 679 799 A (ISUZU CERAMICS RESEARCH INSTITUTE CO., LTD) 2 November 1995 see column 5, line 16 - line 41	1,16,18
A	---	9
A	US 5 088 554 A (ARTERBURY) 18 February 1992 see column 5, line 64 - line 67	1,16
A	FR 2 584 942 A (DOLLFUS & NOACK S.A.) 23 January 1987 see abstract	1,16
	---	
	-/--	

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/EP 96/04887

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 360 358 A (SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V.) 28 March 1990 cited in the application see the whole document ---	16
A	EP 0 310 171 A (SHELL INTERNATIONALE RESEARCH MAATSCAPPIJ B.V.) 5 April 1989 cited in the application see the whole document ---	16
P,X	WO 96 00821 A (QUALITY TUBING, INC.) 11 January 1996 see the whole document -----	1,3

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/EP 96/04887

## Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. claims 1-6, 19, 20
  2. claims 7, 21, 22
  3. claims 8 and 9
  4. claims 10-15
  5. claims 16-18
1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
  2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
  3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
  4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☒ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No  
PCT/EP 96/04887

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9325800 A	23-12-93	AU 672008 B	19-09-96
		AU 4324593 A	04-01-94
		CA 2137565 A	23-12-93
		DE 69305852 D	12-12-96
		EP 0643795 A	22-03-95
		JP 7507611 T	24-08-95
		NO 944746 A	03-02-95
		NZ 253125 A	27-02-96
		US 5366012 A	22-11-94
EP 674095 A	27-09-95	JP 7247784 A	26-09-95
		AU 1366795 A	21-09-95
		BR 9501010 A	24-10-95
		CA 2144014 A	12-09-95
		CN 1111317 A	08-11-95
US 3353599 A	21-11-67	NONE	
US 3270817 A	06-09-66	NONE	
US 1380182 A	31-05-21	NONE	
US 1514062 A	04-11-24	NONE	
US 2812025 A	05-11-57	NONE	
US 5211234 A	18-05-93	AU 653657 B	06-10-94
		AU 3011292 A	05-08-93
		CA 2088292 A	31-07-93
		EP 0553566 A	04-08-93
US 2198573 A	23-04-40	NONE	
US 3153451 A	20-10-64	NONE	
US 3637010 A	25-01-72	CA 930664 A	24-07-73
		US 3741301 A	26-06-73
DE 4126420 C	11-02-93	JP 5269321 A	19-10-93
		JP 7012407 B	15-02-95

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. .onal Application No

PCT/EP 96/04887

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 3633674 A	11-01-72	NONE	
WO 9428284 A	08-12-94	AU 7042194 A CN 1124517 A EP 0699271 A NO 954746 A	20-12-94 12-06-96 06-03-96 23-11-95
US 4434054 A	28-02-84	CA 1196277 A DE 3345796 A GB 2132106 A,B	05-11-85 20-06-84 04-07-84
US 2858894 A	04-11-58	NONE	
US 2835328 A	20-05-58	NONE	
US 2877852 A	17-03-59	NONE	
GB 1455481 A	10-11-76	NONE	
US 2217370 A	08-10-40	NONE	
US 2143072 A	10-01-39	NONE	
DE 3816670 A	29-12-88	EP 0294656 A US 4946310 A	14-12-88 07-08-90
GB 2067425 A	30-07-81	NONE	
US 5226581 A	13-07-93	NONE	
EP 679799 A	02-11-95	JP 7289830 A DE 679799 T US 5560757 A	07-11-95 10-10-96 01-10-96
US 5088554 A	18-02-92	CA 2092308 A CN 1060886 A,B DE 69117966 D DE 69117966 T EP 0553209 A JP 6501069 T	23-04-92 06-05-92 18-04-96 29-08-96 04-08-93 27-01-94

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 96/04887

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5088554 A		US 5293935 A WO 9207167 A US 5190102 A	15-03-94 30-04-92 02-03-93
FR 2584942 A	23-01-87	NONE	
EP 360358 A	28-03-90	AU 615338 B AU 4158989 A CA 1332642 A CN 1031075 B JP 2112413 A US 5045258 A	26-09-91 29-03-90 18-10-94 21-02-96 25-04-90 03-09-91
EP 310171 A	05-04-89	AU 2290888 A CA 1300330 A CN 1034767 A DE 3885996 D DE 3885996 T ES 2047022 T JP 1124617 A KR 9600787 B US H983 H	06-04-89 12-05-92 16-08-89 13-01-94 07-04-94 16-02-94 17-05-89 12-01-96 05-11-91
WO 9600821 A	11-01-96	US 5526881 A CA 2193864 A GB 2304610 A	18-06-96 11-01-96 26-03-97